

Technische Fiche PA-system Sound Support (2020)

FOH system	CODA EV ETX	
MONITORING	8 wedges (Bema loaded) 400 W	
MIXING	DIGICO SD9 for FOH-mix Software Stealth Core 2, last upgrade 24 faders / 1 x 15" touchscreen 8 local inputs 8 local outputs Talkback mic with switch Beyer DT100 headphones	
	APEX Intelli-Q stereo digital 31 bands equalizer-analyzer, AES inserted on master of SD9 Remote controlled bij Apex Intellware EQ software on laptop.	
	3 x CAT 5 connection cables between mix position and stage	
	DIGICO 'Red Box' for network connection SD9-SD11-D-rack	
	DIGICO SD11 for monitormix Software Stealth Core 2, last upgrade 12 faders / 1 x 15" touchscreen 16 local inputs 8 local outputs	
	DIGICO D-rack on stage 32 balanced XLR inputs 16 balanced XLR outputs CAT5 ethercon connection 70 m	
MICROPHONES	Shure (SM58,B58,SM57,B57,B52,B56,B98,B87,KSM8...) AKG (C451, D112, C1000,C419 clip-on...) Sennheiser (MD421,e906, e604...) Neumann (KM184, KMS105...) DPA (4011, 4012, 4018, d-Facto...)	
DI	7 x BSS AR133 3 x stereo APEX dB-DI-2	
Stands	K&M (short boom, long boom...) Black	
Microphone XLR cables	Different lenghts 3m, 5m, 10m, 15m Multi subsnakes 12 ch + 8 ch	